

SPECIFICATION SHEET

HC SERIES KPMF HC610 Water Filtration



APPLICATIONS



- 1 Carbonator
- Volume: Low-Medium

DESIGNED TO

- Improve taste of fountain beverages
- Provide clean ingredient water to your operations
- Reduce chlorine, chloramine*, taste & odor, class 1 particulates, and sediment.

PERFORMANCE

Chloramine Capacity 7,150 gal @ 1.7	
	'GPM*
Min./Max. Pressure 40 - 100 psi	
Min./Max. Temp. 40°- 100°F	
Inlet/Outlet Size 3/4 " FNPT	
Shipping Weight 13 lb	
Dimensions (W/D/H) 14" x 9" x 19"	

Performance may vary based on local water conditions *Tested by 3rd party laboratory to the NSF/ANSI 42 Standard

FEATURES & BENEFITS

- 100% activated Hollow Carbon media. NO binding agents
- Turbo Flow technology evenly distributes water flow and helps to reduce plugging
- Engineered polymer construction for high durability and extended service life
- Minimal pressure drop allows for high flow rates
- Modular design allows for easy capacity expansion



1.800.321.5022 www.KineticoPRO.com WaterCare@KineticoPRO.com



Tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of Chlorine, Taste & Odor and Particulate Class I.